



SYNRye 200

Ideal for high foot traffic areas, this nylon selection is perfect for demanding projects, including playgrounds and rooftops. ASTM Certified E108 Class A Fire-Rated with HeatBlock™ and UV protection reflecting light, which can damage surfaces.

| | |
|------------------------|--|
| SKU | SR200 |
| Grass Zone Yarn/Color | Nylon / Field Green / Olive |
| Grass Zone Denier | 8,400 / 16 |
| Thatch Zone Yarn/Color | Nylon / Turf Green / Tan |
| Thatch Zone Denier | 4,200 / 8 |
| Grass Zone Yarn Shape | Diamond Mono |
| Finished Pile Height | 1 1/8" |
| Finished Pile Weight | 60 oz. |
| Backing | 15 / 18 PP 2-Part / 22oz. EnviroLoc™ |
| Tuft Gauge | 3/8" |
| Total Weight | 88 oz. |
| Tuft Bind | > 8 lbs. |
| Permeability | > 500 inches per / SY |
| Features | EnviroLoc™, HeatBlock™, UV Stabilizers |
| Test Data | ASTM E108 Class A Fire Rating, E648, F1292, F1951, IPEMA Certified |



Unmatched Lifetime Warranty



EnviroLoc™ Plant-Based Backing



Deluster + UV Protection



ASTM E108 Class A Fire Rating

SYNLawn® Artificial Grass

With 1.5 to 2 lbs./sq.ft Infill
Envirofill or Acrylic Sand

Enviroloc Backing System

Exclusive plant-based backing
20% reduction in 'shedding'

Compacted Aggregate Base

90% Compaction of Class II Road Base
2" - 3" of 1/4" Minus Crusher/Inches Mix

6" Non-Galvanized Nails

Inserted 6"-12" apart along perimeter,
3"-5" Staggered along the seams
with seaming cloth and adhesive.



Perimeter Edging
Eco Border, Brick/Paver
or Metal Edging is
required. Existing patio
or walls are sufficient.



Learn more at CADdetails.com

Not to scale. For illustration only.

RECOMMENDED USES



ROOFTOP



LANDSCAPE



PLAY



GOLF

